

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 08-221215

(43)Date of publication of application : 30.08.1996

(51)Int.Cl.

G06F 3/06
G06F 3/06
G06F 12/08
G06F 12/16

(21)Application number : 07-027965

(71)Applicant : FUJITSU LTD

(22)Date of filing : 16.02.1995


(72)Inventor : TAKAHASHI NAKO
TANAKA KEISHICHIROU

(54) EXTERNAL STORAGE CONTROLLER

(57)Abstract:

PURPOSE: To prevent a fault when a bank is degraded by notifying a memory use part of the state of the bank by a memory control part when either one of banks is degraded.

CONSTITUTION: An external storage controller 20 is provided with plural banks where a cache memory 26, control information storage parts 27a and 27b and an involatile memory 28 are divided by the different areas of supply power sources 4a and 4b, and a memory control part (cache control part) 24 performing the control of a memory. By simultaneously writing information in the different banks, the duplex of the memory is performed. When either one of the banks is degraded, the memory control part 24 notifies a memory use part (channel adapter) 21 using the memory of the usable banks. As a result, the memory use part 21 performs an update processing by only the normal banks. Therefore, the writing in the degraded banks can be prevented and the generation of a writing error can be prevented.



LEGAL STATUS

[Date of request for examination] 30.01.2002

[Date of sending the examiner's decision of rejection] 05.10.2004

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]